



PRECITEC - SRICHAKRA CNC LATHES



RAPID 25m/min

ACCURATE

ECONOMICAL

RIGID

SALIENT FEATURES INCLUDE

- ◆ Rigid cast iron torque tube construction main slide base.
- ◆ Slant bed - 60 degree construction.
- ◆ 60 & 110 mm diameter tail stock quill with integral precision live spindle.
- ◆ Hi precision angular contact bearing spindle for speeds upto 6000 rpm with grease and 9300 rpm with oil lubrication. Direct poly V-belt drive for spindle.
- ◆ Admit between centers -400, 800 or 1250 mm for TL 350.
Chuck option also available.
- ◆ Heavy duty L.M. Guides for z-axis and hardened and ground for x-axis with trurcite lining.
- ◆ Various options of speed range and Spindle Power to sit customers job requirement.
- ◆ Easiest access to operator for loading and unloading, tool changing etc.
- ◆ Clear top for easy loading through, Robots Gantry's, Jib Crane's etc.
- ◆ Removable chip tray with Side or Back option for chip conveyer.
- ◆ Modular construction with upgradability to live tools.
- ◆ Heavy-duty 63 & 100 size turrests either electromechanical or hydraulic, bi-directional 8 or 12 station as per customer choice. Live tool option also available.
- ◆ VDI tooling options.
- ◆ Hydraulic steady rests, Auto bar feeding, auto loading robots optionally available.
- ◆ Option of Siemens or Fanuc CNC's.
- ◆ Automatic Centerlised lubrication system.

All Specification is for information only and subjected to change and improvement during development.

S
R
I
C
H
A
K
R
A
T
S
E
R
V
I
S